











100		
General Information		
Product Code	ORS-WHT-105951SPP	
Brand	Essco	
Colour	White	
Туре	Wall Mounted WC - P TRAP	
Material	Ceramic-Vitreous China (VC)	
Product Specification		
Product Dimension	345x485x345 mm	
Bowl Opening (Inner Dimension)	240x310 mm	
Product Net Weight	23 Kg	
Product Gross Weight	27 Kg	
Packaging Dimension	405x385x500 mm	
Outlet	Horizontal	
Inlet Hole And Outlet Hole Dimension	Internal diameter of inlet hole dia. Ø 58 ± 3 mm	
	External diameter of outlet hole dia. Ø 100 ± 5 mm	
Product Features	Beautiful Design In Rectangular Shape For Small Size Bathroom PP Normal Close Seat Cover,Water Usage - 3/6 LPF With Wash Down Flushing Anti Bacterial Glaze on Ceramic,Smooth Glaze Surface,Material - Vitreous China (VC) Product With Complete Genuine Accessories Complete Trap Wash,Box Rim Design	
ACCESSORIES INCLUDED		
Seat cover	ORS-WHT-101S	
Inlet Outlet Gaskit	ZPS-WHT-GK01	
ACCESSORIES RECOMMENDATION		
Rag bolt	ZPS-SNS-RB01 , ZPS-MST-RB02, ZPS-MST-RB07	
Concealed cistern	JCS-WHT-2400S, 2400P, 2400, 2400WS, 2400WP, 2400FS, 2400FP, 2431P, 2431FP, 2431, 2431S, 2431FS	
CARE AND CLEANING GUIDELINES		
		·

- vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use
- ¬ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ¬ Carefully inspect the new product for damage before installation.
- ¬ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ¬ Risk of external leakage. Do not lift or rock the bowl after placement.
- ¬ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- Do not allow cleaners to sit or soak on the product.
- ¬ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ¬ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- n Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- $\neg$  Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

## **QUALITY MANAGEMENT SYSTEM - ISO 9001**



DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. All dimensions are in mm (Tolerance ± 5 MM). Jaquar reserves the right to make the necessary amendments at any time without prior notice. # For Installation Refer Actual Product